

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Article

Product Name: Z-Flex II Products

1.2. Intended Use of the Product

Use of the Substance/Mixture: No use is specified

1.3. Name, Address, and Telephone of the Responsible Party

Company

NEWTEX INDUSTRIES, INC.

8050 Victor-Mendon Road

Victor, New York 14564

(585) 924-9135

1.4. Emergency Telephone Number

Emergency Number : 1-800-836-1001 (USA)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Not classified

2.2. Label Elements

GHS-US Labeling

No labeling applicable

2.3. Other Hazards

The following applies to the product if it is cut, sanded or altered in such a way that excessive and/or significant particulates and/or dusts may be generated: Dust may cause mechanical irritation to eyes, nose, throat, and lungs. Risk of thermal burns on contact with molten product. Vapors from burning may be irritating to the respiratory tract or cause narcosis with symptoms of headache, dizziness and nausea; allergic-type of sensitization may occur with inhalation, causing symptoms of wheezing and shortness of breath.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

General Information:

Mixture of Polyorganosiloxanes, fillers, additives.

Name	Product Identifier	%
Methanol	67-56-1	<0.6%
Titanium Tetrabutanolate	5593-70-4	3-<10%
Aluminum	7429-90-5	Proprietary
Octamethylcyclotetrasiloxane	556-67-1	0.1-<1%
Antimony Oxide (Sb2O3)	1309-64-4	<=6%

Within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]: this mixture is not considered a hazard when used in a manner which is consistent with the labelled directions. This mixture is considered an article in its final form.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: The need for first aid is not anticipated under normal conditions of use.

First-aid Measures After Inhalation: Not expected to be a primary route of exposure. For particulates, dust, or fumes from processing: Move to fresh air.

First-aid Measures After Skin Contact: Gently wash with plenty of soap and water. Do not rub. Not expected to present a significant dermal hazard under anticipated conditions of normal use. Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance.

Z-Flex II Aluminized Products

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Eye Contact: No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

First-aid Measures After Ingestion: If swallowed, do not induce vomiting. Rinse mouth and obtain medical attention if necessary.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/Injuries After Inhalation: For particulates, dust, or fumes from processing: Prolonged contact with large amounts of dust may cause mechanical irritation. Inhalation of vapors and fumes may cause respiratory irritation and sensitization. High concentration of vapors may induce: headache, nausea, dizziness, and shortness of breath.

Symptoms/Injuries After Skin Contact: Direct contact may cause irritation by mechanical abrasion. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Eye Contact: Contact may cause irritation due to mechanical abrasion.

Symptoms/Injuries After Ingestion: Ingestion of large quantities can cause an obstruction causing pain and distress in the digestive tract.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water, spray, foam. Water is the best extinguishing media.

Unsuitable Extinguishing Media: None known.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrogen cyanide. Hydrocarbons.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Accidental release of the product does not present a hazard under normal conditions of use.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use of personal protective equipment is not generally required but should be evaluated based on the extent and severity of accidental release.

Emergency Procedures: Evacuate the area if accidental release presents a significant hazard.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

The product does not pose a significant hazard to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain the product and collect as any solid.

Methods for Cleaning Up: Clean up accidental release immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping as conditions permit.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Further processing of the product requires an evaluation of potential hazards based upon intended use.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Z-Flex II Aluminized Products

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry location. Protect from physical damage.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Ammonia. Amines. Pyridine. Potassium oxides.

7.3. Specific End Use(s)

No use is specified

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Aluminum (7429-90-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (respirable)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

Methanol (67-56-1)		
Type	Exposure Limit Values	Source
REL	200 ppm 260 mg/m ³	NIOSH
PEL	200 ppm 260 mg/m ³	OSHA Z1
TWA	200 ppm 260 mg/m ³	OSHA Z1A
SKIN_DES	- -	ACGIH
STEL	250 ppm 325 mg/m ³	NOISH
SKIN_DES	- -	NIOSH
TWA	200 ppm -	ACGIH
STEL	250 ppm -	ACGIH
STEL	250 ppm 325 mg/m ³	OSHA Z1A
SKIN_FINAL	- -	OSHA Z1A

Antimony oxide (Sb ₂ O ₃) (1309-64-4)		
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen production

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (respirable)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)

8.2. Exposure Controls

Appropriate Engineering Controls

: Engineering controls are not required for normal use of this product.

Personal Protective Equipment

: Personal protective equipment is not generally required but should be evaluated based on conditions of use.

Hand Protection

: Wear protective gloves.

Eye and Face Protection

: Safety glasses recommended for cutting and other operations where particles may be generated.

Skin and Body Protection

: Wear appropriate gloves when handling.

Z-Flex II Aluminized Products

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory Protection	: When manufacturing or handling product in large quantities and dusts or particulates may be generated, maintain airborne concentrations below recommended limits. Workplace risk assessments should be completed before specifying and implementing respirator usage. NIOSH/MSHA approved respirators for protection should be used if found to be necessary.
Other Information	: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Coated film, silver in color
Odor	: No significant odor
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 1.2 – 1.4
Solubility	: Insoluble
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

9.2. Other Information: No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Incompatible Materials:** Strong acids.
- 10.5. Hazardous Decomposition Products:** Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrogen cyanide. Hydrocarbons. This product can form formaldehyde vapors when heated to temperatures above 150 degrees C in the presence of air. Thermal decomposition or combustion may liberate carbon oxides, other toxic gases or vapors and amorphous silica.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: No adverse effects are expected.

Germ Cell Mutagenicity: No evidence of mutagenic effects.

Carcinogenicity: Not classified. (Antimony oxide is bound and sealed in the finished fabric and is not biologically available. Titanium dioxide is bound in the fabric and is not able to become airborne. Thus, the hazards usually associated with titanium dioxide are not applicable to this product.)

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: For particulates, dust, or fumes from processing: Prolonged contact with large amounts of dust may cause mechanical irritation. Inhalation of vapors and fumes may cause respiratory irritation and sensitization. High concentration of vapors may induce: headache, nausea, dizziness and shortness of breath.

Z-Flex II Aluminized Products

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Skin Contact: Direct contact may cause irritation by mechanical abrasion. Risk of thermal burns on contact with molten product.

Symptoms/Injuries After Eye Contact: Contact may cause irritation due to mechanical abrasion.

Symptoms/Injuries After Ingestion: Ingestion of large quantities can cause an obstruction causing pain and distress in the digestive tract.

Chronic Symptoms: None expected under normal conditions of use.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology – General : Not classified

Antimony oxide (Sb2O3) (1309-64-4)	
LC50 Fish 1	>80 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	>1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	>1000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 2	361.5 - 496.0 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
ErC50 (Algae)	67 mg/l

12.2. Persistence and Degradability

Z-Flex® Aluminum Foil Products	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Z-Flex® Aluminum Foil Products	
Bioaccumulative Potential	Not established.

Ethylene bis(tetrabromophthalimide) (32588-76-4)	
BCF Fish 1	0.3 – 1.3

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Consult current IATA Regulations prior to shipping by air.

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Aluminum (7429-90-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 % (dust or fume only)

Antimony oxide (Sb2O3) (1309-64-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	1000 lb

Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Z-Flex II Aluminized Products

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. US State Regulations

Antimony oxide (Sb₂O₃) (1309-64-4)

U.S. - California - Proposition 65 - Carcinogens List

WARNING: This product contains chemicals known to the State of California to cause cancer.

Titanium dioxide (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List

WARNING: This product contains chemicals known to the State of California to cause cancer.

Aluminum (7429-90-5)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

Titanium dioxide (13463-67-7)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision

: 06/29/2021

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

The information herein is given in good faith, but no warranty, expressed or implied is made and we assume no liability from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.

SDS US (GHS HazCom)